

Instructions for poster paper submission

Format-

- Please make your paper in **Microsoft Word**(paper_number.doc) only
- For details like margins, formats etc., please scroll down to view
- A sample paper is also provided in .doc format, please refer **Sample paper.doc**
- File memory size should not exceed 10 MB
- Text, figures and numbers should be in black & white only

Paper Length-

- Maximum – 6 pages

Paper submission-

- Paper should be sent by email only to **sarod07_review@yahoo.co.in**, latest by September 30, 2007.

In case of any difficulty please contact us

Pankaj Priyadarshi
Host Org. Secretary, SAROD-2007,
ADD / ADTG / AERO Entity, VSSC,
Trivandrum - 695 022 (India)
Ph. 91-471-256 4644 (O)
Ph. 91-471-270 4081 (R)
FAX 91-471-256 4097, 270 4134
e-mail: pankaj_priyadarshi@vssc.gov.in

Header on first page
Size 10, italics
Left centred

Paper Size- A4, Font- Times New Roman
Line Spacing-Single

*Symposium on Applied Aerodynamics and Design of Aerospace Vehicle (SAROD-2007)
November 22-23, 2007, Thiruvananthapuram, India*

Title of paper
Size 14, bold

Experimental Investigation of Isolated Hypersonic Inlet

Authors,
addresses and
emails
Size 11

A. Satyanarayana*, MVKV Prasad*, SG Kadam*, SV Ramana[†] and M. Nagarathinam*
Defence Research and Development Laboratory, Hyderabad, India.
(corresponding_author@efgh.ijk)

Size 11,
all caps
bold

ABSTRACT

Wind tunnel tests were conducted in the 340 mm diameter supersonic enclosed free jet wind tunnel on hypersonic air intake model to study the intake starting characteristics. The intake with five different cowl plates was tested. Different cowl plates were used to change the contraction ratio of intake. These tests were carried out at Mach numbers 3.5 and 4.0. Internal pressure distribution on four walls of the intake along its length was measured. Unsteady pressure near cowl entry was also measured. Analysis of intake internal pressure data, cowl unsteady pressure data and flow visualization through color Schlieren clearly show the starting and un-starting of intake with differentiate clearly the starting and un-starting of intake. The measured total pressure recovery is higher than the normal shock pressure recovery for started intake. Contraction ratio required for intake starting is found to be much lower than the theoretical value (normal shock theory).

Abstract text
Single column
Size 9, bold

Key Words: Contraction ratio, pre-compression shock, started and un-started intake

shock wave

NOMENCLATURE

A_{intake} = Cross-sectional area of intake at entry plane

A_{exit} = Cross-sectional area of combustor, 23mm from exit

CR = Contraction Ratio, ratio of throat area to entry area of intake

M_{exit} = Mach number in the combustor, 23 mm from exit

M_{∞} = Free stream Mach number

P = Internal wall static pressure

P_0 = Tunnel stagnation pressure

P_0' = pitot pressure at combustor, 23 mm from exit

\bar{X} = Horizontal distance from the leading edge of the air intake bottom wall, mm

f = Frequency of oscillations of pre-compression

m_{intake} = mass flow rate through intake

m_{∞} = mass flow rate entering the intake at free stream conditions

θ = Angle between cowl internal surface and free stream, degrees

1. INTRODUCTION

Scramjet engines are efficient at hypersonic Mach numbers above 6.0. If the hypersonic flow is decelerated to subsonic speed, which is the case for ramjet combustion, the static temperature rise is very high and addition of heat to the flow is not possible. Also pressure losses as well as wave drag are high due to large deceleration of the flow. Hence scramjet engines are preferred worldwide to power the atmospheric hypersonic vehicles.

Hypersonic air-intake is located on bottom surface of the body of the vehicle, down stream of fore-body ramps and employs a one-step one-time variable cowl to collect and compress free stream air for feeding into the scramjet combustor. Schematic of typical hypersonic vehicle is shown in Figure 1.

2. MODEL MEASUREMENTS

Internal wall static pressures were measured on four walls of the intake. Pressure ports were located along the length at the centerline of the intake. A three-probe pitot rake was used to measure the total pressure near combustor exit (23 mm from exit). Unsteady pressure measurement was made at cowl entry. The pressure port locations are shown in Figure 2. Colour Schlieren pictures were recorded

Heading
Size 11, bold
all caps

Nomenclature
Double Column
Size 10

Heading
Size 11, bold
all caps

Body text
double column
size 10

Page number centred in footer area on
first page

Page number in header area
Left aligned for even pages

Header for even pages
Authors names
Size 10, italics
Centre aligned

with video camera at shutter speed of 1/2000 second to capture the un-steady shock.

3. DISCUSSION OF TEST RESULTS

Internal wall static pressures were measured on four walls of the intake. Pressure ports were located along the length at the centerline of the intake. A three-probe pitot rake was used to measure the total pressure near combustor exit (23 mm from exit).

3.1 Effect of opening of air-intake

Internal wall static pressures were measured on four walls of the intake. Pressure ports were located along the length at the centerline of the intake. A three-probe pitot rake was used to measure the total pressure near combustor exit (23 mm from exit).

4. CONCLUSION

Acknowledgment

REFERENCES

1. Lawrence D. Huebner, Kenneth E. Rock, Edward G. Ruf, and David W. Witte, "Hyper - X Flight Engine Ground Testing for Flight Risk Reduction," Journal of Spacecraft and Rockets, vol.38, No.6, November - December 2001.




Figure 2 Pressure port locations




Figure 3 Unsteady Pressure Measurements




Figure 1 geometry of hypersonic vehicle

Sub-heading
Size 11, bold

Sub-heading
Size 11, bold

Figures and Tables
Double Column

Caption
Size 10, bold




Figure 4 Comparison of bottom plate pressure at $M=3.5$ & 4